

Príloha č.1. – Výkopové schéma včetně dopadové plochy

The drawing shows a trench layout with the following dimensions and features:

- Overall dimensions:** 3500 mm (width) x 6100 mm (length).
- Internal dimensions:** 1750 mm (width of the central section), 3900 mm (length of the central section), and 2400 mm (width of the side sections).
- Radius:** R1550 (radius of the curved end section).
- Angle:** 135° (angle of the curved end section).
- Labels:**
 - BEZPEČNOSTNÍ PROSTOR (Safety Area)
 - Dopadová plocha (Impact Area)
 - 2x VÝKOP 600X600 mm DO HLoubKY 700 mm (2x Trench 600x600 mm to a depth of 700 mm)
 - $S = 19m^2$ (Area)
 - $O = 17m$ (Perimeter)

3900

Dopadová plocha

2400

600

1750

3500

$$\begin{array}{r} 600 \\ \hline \end{array}$$

600

2400

3000

2x VÝKOP 600X600 mm
DO HLoubKY 700 mm

$S = 19\text{m}^2$
 $O = 17\text{m}$

R1550

135.

Príloha č.1. – Výkopové schéma včetně dopadové plochy

The drawing shows a trench layout with the following dimensions and features:

- Overall dimensions:** 3500 mm (width) x 6100 mm (length).
- Internal dimensions:** 1750 mm (width of the central section), 3900 mm (length of the central section), and 2400 mm (width of the side sections).
- Radius:** R1550 (radius of the curved end sections).
- Labels:**
 - BEZPEČNOSTNÍ PROSTOR (Safety area)
 - Dopadová plocha (Impact area)
 - 2x VÝKOP 600X600 mm DO HLoubKY 700 mm (2x Trench 600x600 mm to a depth of 700 mm)
 - $S = 19m^2$ (Area)
 - $O = 17m$ (Perimeter)
 - 135° (Angle of the curved end sections)